



Enirvo Safe Super Performance Cleaners & Polishers

MIRAGE FLOOR POLISH

Polymer Cross linking Technology Versatile Floor Polish

Technical Data Sheet

PRODUCT DESCRIPTION:

Mirage Floor Polish is the most versatile floor finish for all types of flooring surfaces. It is a high performance coating for all types of high wear traffic conditions and is has an easy application with instant first coat gloss, tough, and long lasting.

The product has excellent adhesive qualities and is resistant to black mark, abrasion and scuffing. Finishes the floors less often and save on product and labor cost.

Ideal for use in traditional as well as high speed and ultra high speed burnishing

Recommended Uses:

- **Surfaces:** Resilient Tile, Terrazzo Floor, Brick, Concrete, Sealed Wood, Vinyl, Vinyl Asbestos, Asphalt, Rubber Tile, linoleum and other Hard/Natural Floorings
- Regular or High Speed Buffing Programs
- Schools, Hospitals, Stores, Malls, Offices, Industrial, Commercial, and Residential Areas

Features/Benefits

- High Performance Polymer Technology
- Durable, Mark Resistant Coating
- Use with any Maintenance Program
- High Speed Buffable
- Crystal Clarity
- Versatility of Use

Properties	Rating
Gloss (Initial)	5
Gloss (After buff)	5
Durability	3
Water/Detergent Resistance	5
Leveling	5
Removability/ Strip ability	3

(Ratings apply to typical formulated product. Arbitrary scale 1-5. 5 being the best)

Directions:

Note: Apply with a pre washed, good quality mop or wax applicator. Be sure the mop has not been contaminated with cleaners or strippers

Initial Application

1. Strip all old wax/finish with a good quality product and rinse floor thoroughly to remove every trace of stripping solution. Allow floor to dry completely
2. Apply 2 to 3 coats of finish allowing 20-30 minutes drying time between applications. Time will depend on temperature, humidity and thickness of application

Maintenance:

3. Sweep or dust mop daily. Damp mop daily or as needed to keep floor clean and bright
4. For high speed and ultra high speed maintenance programs, mop or scrub weekly (or more often) using a renovator product. Allow to dry to haze, then burnish to a high shine.

Technical Specifications:

Volume Solids	20%	ASTM D2834
Gloss	92 min.	ASTM D1455
Slip Resistance	Greater than 0.5 Coefficient friction	ASTM D2047
Film	Clear, Non-yellowing, Flexible	
Freeze Thaw Stability	40 to 50 Sq. Mtr. per Ltr/ Coat	ASTM D3209
Leveling	Excellent	
Drying Time	20 mins typical	
Recoat ability	Excellent	ASTM D3153
Detergent Resistance	Excellent	ASTM D3207
Removability	Excellent	ASTM D1792

Special Instructions:

- When using as a foundation for high speed and ultra speed programs, apply additional coats to create a long lasting base
- Protect from freezing
- Keep out of reach of children

PATSA Industrial Products & Services

Head office:

Steel House West Wharf Road,
Karachi-74000, (Pakistan)
Tel: 32201072, 32313113, 32200415
Fax: 92-21-32310976
Email: patsa.industrial@gmail.com

Distribution Office:

70/5 Timber Pond, Kemari,
East Wharf Road, Karachi-75620
Ph: 32856602-32856601
Fax: 32856598

www.patsaonline.com

Disclaimer

The information given in this technical data sheet is only meant as a general product description, based on our experiences and tests and therefore does not represent a specific practical case that has been applied under all possible circumstances. Consequently no liability of Millwala Building Products can be deduced here from. We advise our clients to test the applicability of the product to the nature and the state of the surfaces as well as to the working conditions and to carry out the necessary representative tests in case of doubt.