

Technical Data

JOTAFLOOR NON SLIP AGGREGATE TYPE - FINE / MEDIUM / COARSE



Product description

Jotafloor Non Slip Aggregate is pre-bagged graded, hard wearing aggregate designed to be applied in combination with Jotafloor products to give a non slip floor finish. Aggregate is cast on to wet material and the excess swept off when dry. Coverage depends on quantity initially used and desired profile.

Recommended use

Used where non slip areas are required in locations such as:

- Ramps
- Warehouse aisles
- Food Production Plants
- Dairies
- Production wet areas
- Industrial slippery areas
- Car parks
- Traffic Deck Systems

Comments

Grades: Fine, Medium or Coarse (depending on texture required)
Coverage: 2 – 6 kg/m² gross - 1.5 – 4 kg/m² nett

Physical properties

Flash point Non-flammable

*Measured according to ISO 3233:1998 (E)

Condition during application

According to specifications for the chosen topcoat.

Application methods

Other

If required Jotafloor Non Slip Aggregate can be used with Jotafloor Topcoat, Jotafloor Coating and Jotafloor SL Universal if required. (Advice should be sought from your local Jotun office regarding application techniques as these vary slightly from product to product).

Jotafloor Non Slip Aggregate is cast on to the wet first coat of the Jotafloor material until the whole surface is covered. Aggregate should not be thrown onto the wet coating as this may damage the first coat. Distribute the aggregate from a container eg. distribution sieve, that will allow the aggregate to fall directly onto the wet coating.

Once the first coat has dried, remove the excess aggregate from the surface by vacuum or sweeping brush for reuse if clean.

Apply the final coat of Jotafloor material to the desired thickness.

Storage

The product must be stored in accordance with national regulations. Storage conditions are to keep the containers in a dry, cool, well ventilated space and away from source of heat and ignition. Containers must be kept tightly closed.

Handling

Handle with care. Stir well before use.

Packing size

Jotafloor Non Slip Aggregate Fine, Medium and Coarse supplied in 25 kg bags. Packing may vary from country to country according to local requirements.

Health and safety

Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

For detailed information on the health and safety hazards and precautions for use of this product, we refer to the Material Safety Data Sheet.

DISCLAIMER

The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control, we cannot guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice.

Head Office & Nordic

Jotun Paints
P.O. Box 2021
N-3248 Sandefjord
Norway
Phone +47 33 45 70 00
Fax +47 33 46 46 13

Europe

Jotun Paints (Europe) Ltd.
Stather Road, Flixborough
North Lincolnshire DN15 8RR
United Kingdom
Phone +44 172 44 00 000
Fax +44 172 44 00 100

Middle East

Jotun U.A.E Ltd. LLC.
Al Quoz Industrial Area
P.O Box 3671
Dubai U.A.E
Phone +971 4 3 39 50 00
Fax +971 4 3 38 06 66

South East Asia

Jotun (Singapore) Pte. Ltd.
No 11-15, Sixth Lok Yang
Road
Jurong
Singapore 628 111
Phone +65 6265 4711
Fax +65 6265 7484

Jotun is a World Wide company with factories, sales offices and stocks in more than 50 countries. For your nearest local Jotun address please contact the nearest regional office or visit our website at www.jotun.com

ISSUED 13 FEBRUARY 2002 BY JOTUN PAINTS
THIS DATA SHEET SUPERSEDES THOSE PREVIOUSLY ISSUED