

MATERIAL SAFETY DATA SHEET

MSDS

Last changed: 02/02/2000

Internal num.: 01

Replaces date:23/10/1997

JOTAGUARD 85 - COMP. A

1. PRODUCT AND COMPANY

TRADE NAME : JOTAGUARD 85 - COMP. A
APPLICATION : Two-pack epoxy coal-tar coating.
ART-No : M3205

PRODUCER/IMPORTER :

Company : JOTUN-HENRY CLARK LTD.
Address : Flixborough, Scunthorpe
Zip & city : North Lincolnshire DN15 8RR
Country : UK
Telephone : +44 1724 40 00 00
Fax : +44 1724 40 01 00
Emergencyphones : Contact the National Poison Center
Contactperson : QA/Environm. dept., JOTUN A/S, NORWAY
Responsible : QA/Environm. dept., JOTUN A/S, NORWAY

2. COMPOSITION OF PRODUCT

No	Ingredients name	CAS-NO	Weight%		Dangerclas./Cmnt.
1	XYLENE, mixed isomers	1330-20-7	10-25	N	Xn,10-20/21-38
2	BENZO(B)FLUORANTHENE	205-99-2	0,1-1		K2,45
3	BENZO(A)ANTHRACENE	56-55-3	0,1-1		K2,45
4	BENZO(A)PYRENE	50-32-8	0.1-1		K2 M2 R2,45-46-47

Legend: T+=Very toxic, T=Toxic, C=Corrosive, Xn=Harmful, Xi=Irritant, IK=No classification required, E=Explosive, O=Oxidising, F+=Extremely flammable, F=Very flammable, Fo=Flammable, N=Dang. to the environment,

INGREDIENT COMMENTS

Substances presenting a health hazard within the meaning of the current issue of the CHIP Regulations or assigned occupational exposure limits.

3. HAZARD IDENTIFICATION



MAY CAUSE CANCER. MAY CAUSE HERITABLE GENETIC DAMAGE.
 FLAMMABLE.
 HARMFUL BY INHALATION AND IN CONTACT WITH SKIN.
 For potential danger for the environment, see section 12.

4. FIRST AID

INHALATION

Keep the patient warm in a quiet place with fresh air. If breathing has stopped, administer artificial respiration. If unconscious place in the recovery position. Seek medical advice.

SKIN CONTACT

Remove contaminated clothing. Wash skin thoroughly with soap and water or use an appropriate skin cleaner. Do NOT use solvents or thinners.

EYE CONTACT

Remove any contact lenses. Hold the eyelids apart. Irrigate copiously with clean, fresh water for at least 10 minutes. Seek medical advice if symptoms persist.

INGESTION

DO NOT INDUCE VOMITING. If accidentally swallowed obtain immediate medical attention. Keep at rest. Seek medical advice.

MEDICAL INFORMATION

Risk of chemical pneumonia by aspiration. Keep attention: danger of lung damage. General health examination. Professional evaluation of the work station.

5. FIRE FIGHTING MEASURES

PROPER FIREFIGHTING EQUIPMENT

Recommended: alcohol resistant foam, CO₂, powders, water spray. Not to be used: water jet.

FIRE AND EXPLOSION HAZARDS

Decomposition products may be a hazard to health. Fire will produce dense black smoke containing hazardous products of combustion (see Section 10).

PERSONAL PROTECTION WHEN FIREFIGHTING

The personal protective equipment required is provided in section 8. Professional fire-fighters are required to use an air-fed system when dealing with major fires.

OTHER INFORMATION

Do not allow run-off from fire fighting to enter drains or water courses. Cool closed containers exposed to fire with water.

6. ACCIDENTAL RELEASE MEASURES

OTHER INFORMATION

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8. Place in container for disposal according to local regulations (see section 13). Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite and diatomaceous earth. Do not allow to enter drains or watercourses. Clean preferably with a detergent; avoid use of solvents. If the product enters drains or sewers, the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the Environmental Agency.

7. HANDLING AND STORAGE

HANDLING ADVICE

The Manual Handling Operations Regulations may apply to the handling of containers of this product. Electrical equipment should be protected to appropriate standards. Never use pressure to empty the container, it is not a pressure vessel. Always keep in containers made of the same material as the supply container. For personal protective equipment see Section 8. Smoking, eating and drinking are forbidden in the work area. Avoid inhalation of vapour and spray mist. Avoid skin and eye contact. Use non-sparking tools. Keep container tightly closed. Exclude sources of heat, sparks and open flame. Floors should be electrically conductive. Personnel should wear anti-static clothing and footwear. Always use earth (ground) wire when transferring from one container to another. The product may charge electrostatically. Use explosion-proof electrical equipment. The product should not be used in vicinity of open flames or other sources of ignition. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Vapours may form explosive mixtures with air. Vapours are heavier than air and may spread along floors.

STORAGE

Containers which are opened should be properly resealed and kept upright to prevent leakage. No smoking. Store separately from oxidising agents and strongly alkaline and strongly acidic materials. Store in a dry, cold and well ventilated place away from sources of heat, ignition and direct sunlight. Observe the label precautions. Store in accordance with the regulations for flammable materials.

8. EXPOSURE CONTROL/PERSONAL PROTECTION

OEL s

Ingredients name	CAS-no	OEL value	OEL
XYLENE, mixed isomers	1330-20-7	441,0 mg/m ³ ;Sk 662,0 mg/m ³ ;Sk	LTEL STEL

RESP. PROTECTION

When use of roller or brush, then charcoal filter is sufficient. Gas mask with combined filter (dust filter P3/gas filter A2) may be sufficient when spraying.

EYE PROTECTION

Eye protection designed to protect against liquid splashes should be worn.

HAND PROTECTION

Use PVA/viton gloves. Barrier creams may help to protect exposed areas of the skin but are not substitutes for full physical protection. Never apply barrier cream to contaminated skin.

SKIN PROTECTION

Wear anti-static clothing made of natural fibre or of heat resistant synthetic fibre. When spraying use suit covering the whole body.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form:	Liquid.		
Colour:	Black. Brown.		
Odour:	Organic solvent.		
Solubility:	Organic solvent.		
Melting point/range:	-	Density:	1.4
Expl. limit LEL-UEL%:	1.10 - 7 -	Boiling point/range:	138 - 144°C
Flash point:	28°C	pH concentrate:	-
Ignition temp.:	525°C		

10. STABILITY AND REACTIVITY

STABILITY

Stable under recommended storage and handling conditions (see section 7).

MATERIALS TO AVOID

Keep away from oxidising agents, strongly alkaline and strongly acidic materials to prevent the exothermic reactions.

HAZARDOUS DECOMPOSITION PRODUCTS

In a fire, hazardous decomposition products such as smoke, carbon monoxide, carbon dioxide and oxides of nitrogen may be produced.

11. TOXICOLOGICAL INFORMATION

GENERAL

There are no toxicological data available on the product itself. The product contains carcinogenic substances. The product contains substance toxic to reproduction. The product contains mutagenic substance.

INHALATION

Exposure to organic solvent vapours may result in adverse health effects such as irritation of the mucous membrane and the respiratory system and adverse effects on the renal and central nervous system. Symptoms and signs include headache; dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

SKIN CONTACT

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to the product's defatting properties.

EYE CONTACT

Splashes in the eyes may cause irritation and reversible local damage.

INGESTION

Absorbed by the gastric intestinal system. May cause liver and kidney damage. Accidental ingestion may cause vomiting and abdominal pains. Risk of chemical pneumonia.

12. ECOLOGICAL INFORMATION

OTHER INFORMATION

Do not discharge the product to sewer or drains.

13. DISPOSAL

Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act. Do not allow into drains or water courses. Waste must be disposed of at approved landfill/waste storage or treatment facility.

WASTEGROUP

08 00 00 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVE, SEALANTS AND PRINTING INKS. 08 01 02 Waste paints and varnish free of halogenated solvents.

14. TRANSPORT INFORMATION

PROPER SHIPPING NAME		PAINT	
IMDG (Sea)			
UN No	1263	Class	3.3
Label	3	Packaging Group	III
EmS	3 - 05	MFAG	310
Page	3372		

Transport only in accordance with ADR for road, RID for rail, IMDG for sea transport and IATA for airtransport. Not ADR-restricted ref. NOTE under E of marginal 2301 (applicable to receptacles of less than 450 litres capacity).

15. REGULATORY INFORMATION

Classif.:



COMPOSITION

XYLENE, mixed isomers (10-25), BENZO(B)FLUORANTHENE (0,1-1), BENZO(A)ANTHRACENE (0,1-1), BENZO(A)PYRENE (0.1-1)

R-PHRASES

R45 May cause cancer. R46 May cause heritable genetic damage. R10 Flammable. R20/21 Harmful by inhalation and in contact with skin.

S-PHRASES

S23 Do not breathe vapour/spray. S36/37 Wear suitable protective clothing and gloves. S38 In case of insufficient ventilation, wear suitable respiratory equipment. S45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Restricted to professional users. Attention - Avoid exposure - obtain special instructions before use.

REFERENCES

The product is labelled for supply in accordance with the current issue of CHIP Regulations, and latest version of the approved supply list.

16. OTHER INFORMATION

ISSUED:03/02/2000

INFORMATION SOURCES:**USER NOTES**

This document was generated by use of 10/1/99 11:24 - MSSQL Server- build:64 (Chemical- ,Health- and Enviromental Safety System)http://www.terosafe.no