

ACRYOXIDE

Anti-Corrosive Protective Primer with
Active Inorganic Corrosion Inhibitors



**An Industrial Care
Company**

Tel: 021-32201072 Email: Patsa.industrial@gmail.com
Web: www.patsaonline.com

Technical Data Sheet

PRODUCT DESCRIPTION:

A general purpose quick drying anti-corrosive metal primer based on 100% pure acrylic resins and red oxide pigments.

USES

Suitable for interior or exterior use on steel substrates as primer in mild to moderately corrosive (industrial and marine) environments

PROPERTIES:

RESIN TYPE: 100% pure Acrylic
SPECIAL PROPERTY: Quick Drying
FINISH: Egg Shell
COLOR: Red/Brown
SOLIDS BY VOLUME: 57.0% ± 2%

SURFACE PREPARATION

All surfaces must be clean, dry, and free from dirt, dust, loose rust, stains, grease, oil, wax, and other contaminants. Remove all loose, peeling, or chalky paint by sanding, scraping, high-pressure washing, sandblasting or other appropriate methods. Glossy surfaces should be sanded to provide a roughened surface for good adhesion.

SPECIAL INSTRUCTIONS

Always wear appropriate personal protective equipment during surface preparation, and finish clean up of any residues by solvent-wiping all surfaces.

Sandblasted or newly cleaned metal must be prime-coated the same day to prevent recontamination.

RECOMMENDED FILM THICKNESS PER COAT

Wet: 85 microns
Dry: 50 microns

SPREADING RATE

Up to 12 sq. mtr / ltr.
(Depending on surface profile and application method)

AVERAGE DRY

Surface dry in 1 hour, re-coatable after 6 hours
(in normal drying conditions)

APPLICATION EQUIPMENT

Brush, Roller, Airless spray

PACKAGING

5 liter & 20 liter containers

THINNING RECOMMENDATIONS

Brush and Roller: 0– 5% Thinner # 7
Air spray and Airless Spray: 0–10% Thinner # 7

STORAGE

Store in a dry area. Protect from freezing. Extreme temperatures may cause paint to become unusable. For example: Freezing and thawing may cause paint to gel, and high heat may cause a solid skin to form

CLEANUP

Paint thinner, where allowed. Dispose of waste in accordance with all applicable laws and regulations.

IMPORTANT NOTICE

These products are sold subject only to the expressed warranties contained herein. Additional warranties, expressed or implied, and any warranty of merchant ability is hereby excluded. Buyer agrees that seller assumes no liability for consequential damages of any kind, which result from the use or misuse of the merchandise sold hereunder. In the event that the buyer proves that any goods received do not conform to the specifications agreed to between the parties or if the buyer proves that such goods were defectively manufactured. The buyer's remedies shall be limited to either the return of the goods and repayment of the purchase price or replacement of the non-conforming goods at the option of the seller. Such remedy being exclusive of all others and the sole remedy available to the buyer, hereby expressly waives any claim to additional damages.

PATSA Industrial Products & Services

Head office:

Steel House West Wharf Road,
Karachi-74000, (Pakistan)
Tel: 32201072, 32313113
Fax: 92-21-32310976
Email: patsa.industrial@gmail.com

Distribution Office:

70/5 Timber Pond, Kemari,
East Wharf Road, Karachi-75620
Ph: 32856602-32856601
Fax: 32856598