

# Aquafill

## Wall Filler



Steel House, West Wharf Road, Karachi-74000, Pakistan. Tel: (92-21) 2856601 Fax: (92-21) 2856598

A ready mixed interior filler with easy sanding properties for the filling of cracks, holes and the smoothing of uneven surfaces.

### USES

Suitable for interior use only, as a thin coat putty for the finishing of rough surfaces and as a filler for small cracks, holes and surface imperfections. Also suitable for repair work to interior plaster, fair – faced and lightweight concrete.

### PROPERTIES

#### Appearance

Flat

#### Volume Solids

73% ± 2%

#### Colour

White

#### Pack Size

5 liters metal cans.

#### Spreading Rate

3.2 sq. mtr. / kg / at 100 DFT Depending on end use application method and thickness applied.

#### Drying Time

Surface dry in 1 hour. Re-coatable with itself after 2 hours and paintable after 10 hours. (in normal drying conditions).

#### Shelf Life

12 Months when stored in dry and cool conditions.

### APPLICATION DATA

Mix well before use. Apply by trowel, filling knife or spray. For details of spray equipment contact PATSA Technical Service Department.

#### Thinning

Do not thin, supplied ready for use.

#### Cleaning

Clean all tools and equipment immediately after use with clean water.

#### Caution

Do not use when humidity levels may cause surface condensation (maximum 85%), during rainy conditions or if

temperatures are likely to fall below 5°C during application and drying. Protect from frost.

### SPECIFICATION

#### Preparation (New and Previously Decorated Surfaces)

##### All Interior Surfaces

All surface should be sound, clean, dry and free from loose and flaking material, dirt, efflorescence, oil, curing compounds, from release agents, laitance and organic growth.

See Notes [i, ii]

Unstable surfaces (powdery or chalky) should receive a coat of the appropriate PATSA AQUAPRIME before filling. Application (New and Previous Decorated Surfaces) All Interior Surfaces Apply sufficient AQUAFILL to fill or smooth surface.

See Notes [iii, iv]

### NOTES

- i. Organic growth (moss, fungus, mildew) should be treated with GloFlo QUAT BAF in accordance with manufacturer's instructions.
- ii. New cement, plaster and concrete must have had ample opportunity to dry before filling (average 15 days)
- iii. On very dry absorbent surfaces wet the surface with a sweet water prior to using the filler.

### SAFETY INFORMATION

Use only in well ventilated areas. In case of sufficient ventilation during spraying, wear suitable respiratory equipment. Do not breath vapour / spray.

In case of contact with eyes, rinse immediately with plenty of sweet water and seek medical advice. Keep out of reach of children.