



# AQUASHIELD TEX

## Flexible Paint System



An Industrial Care  
Company

Tel: 021-32201072 Email: Patsa.industrial@gmail.com

Web: www.patsaonline.com

### Technical Data Sheet

#### PRODUCT DESCRIPTION

Aquashield Tex is a flexible elastomeric paint which provides an excellent restoration and preventive coating for surfaces subjected to cracks. Aquashield Tex is a semi gloss medium texture coating based on high quality 100% acrylic water based binder.

#### PRODUCT BENEFITS:

- Concrete Protection
- Low Dirt Retention
- Fungi/Algae Resistance
- High Flexibility and Tensile Strength
- Water Vapor Transmission

#### RECOMMENDED USE

Aquashield Tex is a specialty membrane system recommended for new and previously painted concrete, brick and building façade exposed to harsh climatic conditions, including seaside and coastal environments.

The coating can be used on exterior and interior level on all types of cement plaster and concrete surfaces due to its weather and water, anti carbonation, anti chlorination and water vapor resistance properties.

Aquashield Tex provides an attractive soft texture that will hide and cover minor imperfections in the surface when applied with a sponge roller. The product has good crack bridging ability in excess of 2 times its original shape.

#### PHYSICAL PROPERTY

Colour: Patsa color card  
 Gloss: Semigloss  
 Water resistance: Very good  
 Flexibility: Very good

#### SURFACE PREPARATION

The substrate must be sound, clean, dry, free from dust, oil, grease and laitance etc. All traces of release agents

must be removed. On chalky and dusty surfaces, all loose material must be removed by stiff bristle brushing.

#### Other surfaces

The coating may be used on other substrates. Please contact your local PATSA office for more information.

#### APPLICATION METHODS

Spray: Airless spray, Conventional spray or Hopper Gun.  
 Brush: Recommended.  
 Roller: Sponge roller.  
 Thinner/Cleaner: Water

#### TYPICAL PAINT SYSTEM

##### On porous and chalky surfaces:

Uniprime-P	1 coat
Aquaprime	1 coat
<b>Aquashield Tex</b>	<b>2 coats</b>

##### On new surfaces and old, sound paint surfaces:

Aquashield Tex (thinned 20%)	1 coat
<b>Aquashield Tex</b>	<b>2 coats</b>

##### On new concrete, as a concrete protection system:

Acryseal HS	1 coat
<b>Aquashield Tex</b>	<b>2 coats</b>

Other systems may be specified, depending on area of use

**Typical Coverage:** 60 to 80 sq. ft. per gallon

#### PACKING SIZE

1 gallon  
4 gallon



Resists crack buildup

## SAFETY

Use under well ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

## STORAGE

The product must be stored in accordance with national regulations. The product must be kept in a cool and well ventilated place, protected from heat and direct sunlight. Containers must be kept tightly closed.

## IMPORTANT NOTICE

These products are sold subject only to the expressed warranties contained herein. Additional warranties, expressed or implied, and any warranty of merchant ability is hereby excluded. Buyer agrees that seller assumes no liability for consequential damages of any kind, which result from the use or misuse of the merchandise sold hereunder. In the event that the buyer proves that any goods received do not conform to the specifications agreed to between the parties or if the buyer proves that such goods were defectively manufactured. The buyer's remedies shall be limited to either the return of the goods and repayment of the purchase price or replacement of the non-conforming goods at the option of the seller. Such remedy being exclusive of all others and the sole remedy available to the buyer, hereby expressly waives any claim to additional damages.



### **PATSA Industrial Products & Services**

**Head office:**

Steel House West Wharf Road,  
Karachi-74000, (Pakistan)  
Tel: 32201072, 32313113  
Fax: 92-21-32310976  
Email: [patsa.industrial@gmail.com](mailto:patsa.industrial@gmail.com)

**Distribution Office:**

70/5 Timber Pond, Kemari,  
East Wharf Road, Karachi-75620  
Ph: 32856602-32856601  
Fax: 32856598