

AQUASILK

Interior / Exterior Finish



An Industrial Care
Company

Tel: 021-32201072 Email: Patsa.industrial@gmail.com

Web: www.patsaonline.com

Technical Data Sheet

PRODUCT DESCRIPTION

A high quality decorative wall finish based on 100% acrylic copolymer emulsion with medium sheen / silky finish. Paint finish shows highly washable property, stain resistance, and resistance to yellowing.

USES

Suitable for interior & exterior surfaces such as cement, plaster, concrete, brick, stucco, gypsumboard, building boards.

Particularly suitable in areas subject to condensation and wear & tear such as kitchens, bathrooms, corridors, hallways and public areas.

PROPERTIES

Appearance: Silk

Color Range: Brilliant white

PATSA Color range "Freedom of color choices"

Volume Solids: 52% ± 2%

Pack Size: 5 liters and 20 liters

Spreading Rate: Up to 13 sq. mtr. /liter

(depending on surface texture, porosity and method of application)

Drying Time: Surface dry in 1 hour. Recoatable after 3 hours (in normal drying conditions)

Shelf Life: 2 years when stored in dry and cool condition

APPLICATION DATA

Stir well before use. Apply by brush, roller, air spray or airless spray. For details of spray equipment, contact PATSA Technical Services Department.

Thinning

Brush and Roller: 5% sweet water (The first coat may be thinned up to 10% on very absorbent surfaces). Air spray and Airless spray: 10% sweet water.

Cleaning

Clean all tools and equipment immediately after use with clean water.

Caution

Do not use when humidity levels may cause surface condensation (maximum 85%), during rainy conditions or if temperatures are likely to fall below 5°C during application. Protect from frost

SPECIFICATION

Surfaces Preparation (New and Previously Decorated Surfaces)

General

All surfaces should be sound, clean, dry and free from loose and flaking material, dirt, efflorescence oil, grease, wax and polish. When appropriate the relevant PATSA Primer should be used. Fill small cracks and surface imperfections with PATSA AQUAFILL, larger cracks may be filled with ASOCRET RN. See notes [i, ii]

Exterior Concrete, Brick, Render, Plaster, Gypsum board, Fiberboard etc.

Prime with one coat of AQUAPRIME. Allow to dry. See notes [i, ii, iii]

Decoration (New Work and Previously Decorated)

All surfaces

Apply two coats of PATSA AQUASILK. See notes [iv, v]



NOTES

- i.** Organic growth (moss, fungus, mildew) should be treated with a proprietary fungicidal treatment in accordance with manufacturer's instructions.
- ii.** On previously decorated surfaces, after the removal of loose and flaking material apply PATSA AQUAPRIME to bare areas overlapping onto the existing decoration.
- iii.** Surfaces of high porosity (very chalky and powdery) should be primed with one coat of AQUAPRIME
- iv.** For interior surfaces thin first coat to satisfy the porosity of the surface, a third coat may be required on very porous surfaces. Do not use in heated surfaces.
- v.** A third coat may be required if there is marked color contrast between the surface and the paint to be applied.

SAFETY INFORMATION

Use only in well ventilated areas. In case of insufficient ventilation during spraying, wear suitable respiratory equipment. Do not breathe vapor / spray. In case of contact with eyes, rinse immediately with plenty of sweet water and seek medical advice. Keep out of reach of children.

IMPORTANT NOTICE

These products are sold subject only to the expressed warranties contained herein. Additional warranties, expressed or implied, and any warranty of merchant ability is hereby excluded. Buyer agrees that seller assumes no liability for consequential damages of any kind, which result from the use or misuse of the merchandise sold hereunder. In the event that the buyer proves that any goods received do not conform to the specifications agreed to between the parties or if the buyer proves that such goods were defectively manufactured. The buyer's remedies shall be limited to either the return of the goods and repayment of the purchase price or replacement of the non-conforming goods at the option of the seller. Such remedy being exclusive of all others and the sole remedy available to the buyer, hereby expressly waives any claim to additional damages.



PATSA Industrial Products & Services

Head office:

Steel House West Wharf Road,
Karachi-74000, (Pakistan)
Tel: 32201072
Fax: 92-21-32310976
Email: patsa.industrial@gmail.com

Distribution Office:

70/5 Timber Pond, Kemari,
East Wharf Road, Karachi-
75620
Ph: 32856602-32856601
Fax: 32856598