

Seal-Once

Long Lasting & Deep Penetrating Formula for Surface Sealing



An Industrial Care
Company

Technical Data Sheet

PRODUCT DESCRIPTION

Seal-Once sealer is an advanced aqueous formula designed primarily for waterproofing wood, concrete and masonry and composite decking. Seal-Once provides years of protection and does an exceptional job of limiting moisture ingress, as well as reducing fungal and microbial attack by reducing available moisture. Seal-Once is colorless and will not discolor wood, concrete or masonry. Seal-Once is available in clear and tinted formulas by adding one package of tint per gallon.

PRODUCT BENEFITS:

Contains no toxins or heavy metals

Seal-Once does not contain nitrates or phosphorous compounds. Seal-Once also does not contain any aluminum, arsenic, barium, cadmium, chromium, copper, lead, mercury or other heavy metals. It does not contain silica. There is an internal chemistry which is designed to facilitate bonding to wood and cementitious substrates.

Approved safe for use over fresh and saltwater

When Seal-Once dries on a substrate, it does not leach out or become hydrolytically unstable, however it may be removed by wearing the substrate away or by application of strong oxidizers.

PHYSICAL CHARACTERISTICS

Color	Milky White
Flash pt.	None
pH	7.4
Solvents	None
Specific Gravity	0.993
Application Temp.	35°F and above
Solid Content	30%+

Recommended Usage

Wood: (all types), Decks, Fences, Docks, Piers, Shingles, Shingle Siding, Wood Playgrounds

Concrete: Walkways, Driveways, Curbs, Steps, Platforms, Loading Docks, Ramps, Floors, Parking Decks

Other: Stucco, Brick, Tile (Unglazed), Limestone, Granite, Slate, natural stones

FEATURES

- Water-Based and Non-Flammable
- Contains No TAPS/HAPS (Toxic/Hazardous Air Pollutants)
- VOC Content N/A, Non-Ozone Depleting
- Not Regulated by Authorities for Worker Health and Safety
- Not Regulated by Authorities for Transportation and Storage
- Will Not Harm Fish, Plants, Pets or Livestock
- Will Not Burn Skin; Odorless

BENEFITS

- Reduces Fungal Microbial Attack
- Will Not Discolor Wood or Masonry Surfaces
- UV Transparent, Paintable or Stainable
- Excellent Durability to Weathering
- Excellent Longevity, Preserves Wood
- Reduces Spalling and Cracks Caused by Moisture
- Outperforms Other Sealers and Stains
- Cost Effective

APPLICATION : By Roller or Brush

SAFETY INFORMATION

Use only in well ventilated areas. In case of insufficient ventilation during spraying, wear suitable respiratory equipment. Do not breathe vapor / spray.

In case of contact with eyes, rinse immediately with plenty of sweet water and seek medical advice. Keep out of reach of children.



PATSA Industrial Products & Services

Head office:

Steel House West Wharf Road,
Karachi-74000, (Pakistan)
Tel: 32201072
Fax: 92-21-32310976
Email: patsa.industrial@gmail.com

Distribution Office:

70/5 Timber Pond, Kemari,
East Wharf Road, Karachi-75620
Ph: 32856602-32856601
Fax: 32856598

www.patsaonline.com