

SCHOMBURG GmbH & Co. KG
Aquafinstraße 2-8
D-32760 Detmold - Germany
phone +49-5231-953-00
fax +49-5231-953-108
mail export@schomburg.de
web www.schomburg.de/en



Technical Data Sheet

ASOL-FE

Art.-No. 2 02840

Bituminous protection layer - non-polluting bituminous emulsion

Properties:

ASOL-FE is a protective coating resistant to earth moisture and aggressive media in soil. For concrete, plaster or masonries of cellars, walls, foundations and shafts.

Areas of application:

ASOL-FE is used as a protection layer on concrete, plaster or masonry of cellars, walls' foundations, pits etc,. It is resistant to natural aggressive media.

Technical Data:

Basis:	bitumen
Colour:	brown black
Density:	1.06 - 1.10 g/cm ³
Hardening:	air curing
Priming:	not necessary
Consumption:	200 - 250 ml/m ² and layer min. 2 layers
Pot life:	from + 2° C to +35° C
Storage:	free from frost 12 month
Cleaning:	Clean tools immediately after use with water or ASO-Kaltreiniger.

Surface preparation:

The surface must be clean, free from oil or grease, even and sound.

Product preparation:

ASOL-FE will be painted, rolled or sprayed onto the surface. The first layer should be dry before the second one is applied to obtain a fast curing. Protect wet layers from frost.

Important advice:

Protect surfaces which shall not be coated.
Avoid contact with eyes or skin. In case of eye contact with ASOL-FE clean thoroughly with water and consult a physician.