



## Technical Data Sheet

# ASOLIN-K

Art.-No. 2 01110

## Hydrophobic Waterproofing Admixture for Concrete and Mortar

### Properties:

- Plasticising.
- Prevents the formation of gravel pockets and segregation.
- Increases the resistance to aggressive influences.

### Areas of application:

ASOLIN-K is a water repellent waterproofing agent for concrete, cement and cement-lime mortars. It is suitable for producing water impermeable, non-reinforced concrete as well as waterproof renders against driving rain and ground damp. The risk of moisture damage is greatly reduced through the addition of ASOLIN-K and the life expectancy of the building is considerably extended.

### Technical Data:

Density:	approx 1.06 g/cm <sup>3</sup>
Consistency:	liquid
Freezing point:	- 2° C
Consumption:	0.4 % according to the binding agent (water proof concrete approx. 1.2 to 1.5 kg/m <sup>3</sup> mortar approx. 2.0 to 2.5 kg/m <sup>3</sup>
Packaging:	1.000, 25, 10 or 1 kg packs
Storage:	in closed packs free from frost, unlimited storage

### Product preparation:

ASOLIN-K is either mixed with water or the appropriate mixing material. Due to its plasticising effect the appropriate water saving must be taken into consideration. Produce concrete conforming to DIN EN 206. Carry out appropriate pre-trials.