



BLANKOL-2000

Universal Concrete Release Agent

Art.-No. 4 06130

Properties and Benefits:

BLANKOL-2000 is a high-quality release agent which can be used for various purposes. Due to its low viscosity it is very economical in use.

BLANKOL-2000 dries up quickly and leads, in case of proper application, to very even, spot- and pore-free surfaces with sharp edges and details.

BLANKOL-2000 acts anti-corrosive, is not hydrophing and allows a later finishing with plasters etc.

Fields of Application:

BLANKOL-2000 has been particularly designed for the precast element production. It can be applied on all non-absorbing moulds, even when heated up to + 60° C. BLANKOL-2000 achieves very good results with remarkable fair-faced concrete quality, particularly when used on high vertical moulds.

The agent's very short drying time (up to 4 minutes) reduces the circulation times of the moulds.

Technical Data:

Colour:	light yellow
Form:	liquid
Density:	0.78 g / cm ³
Storage:	keep away from intense heat, not frost sensitive
Shelf-life:	12 months in closed original containers at + 20° C
Packaging:	1000 l IBCs 180 l drums 25 l cans

Consumption:

15 - 25 g/m²

Instructions for use:

BLANKOL-2000 is delivered ready-for-use and is to be sprayed evenly and in a thin layer onto the clean and dry mould by means of a spraying device with a nozzle especially suitable for this material.

Special Advice:

- Suitability tests should be carried out prior to usage.
- Welding, flying sparks, open fire etc. must be absolutely avoided next to freshly sprayed moulds.
- Avoid puddles!
- Excessive coating can lead to incrustations and build-ups.

Safety Regulation:

Please adhere to the European Safety Data Sheet (MSDS)!