

SCHOMBURG GmbH & Co. KG
Aquafinstraße 2-8
D-32760 Detmold - Germany
phone +49-5231-953-00
fax +49-5231-953-108
mail export@schomburg.de
web www.schomburg.de/en



Technical Data Sheet

FIX 10-M

Construction Cement

Art.-No. 2 01818

Properties:

FIX 10-M is a chloride free quick setting construction cement compatible with all standard cements according to DIN 1164. FIX 10-M is suitable as a fast setting additive for all plaster and concrete works.

The potential bonding strength allows the addition of sand (1 part FIX 10-M to 1 - 2 parts sand by volume). The curing process will not decrease, the strength will be almost the same after addition of the sand. The curing depends on the temperature.

Areas of application:

Suitable for the fast filling of holes, for the anchoring and fixing of machinery, piping, railings etc.. For all exterior and interior connector joint sealing and fast repairing on concrete, artificial and natural stone, plaster, screed or masonry surfaces.

Technical Data:

Basis:	Cement
Bulk weight:	1.1 kg/dm ³
Curing:	After 20 min.
Packaging:	1, 6 and 12 kg buckets
Storage:	dry and air tight up to 12 months

Surface preparation:

Loose plaster and masonry particles have to be removed. The clean surface is wetted with water.

Product preparation:

In a clean vessel the powderous FIX 10-M is added to water.

FIX 10-M must be mixed and processed fast. Do not mix more FIX 10-M than can be processed in this time. After addition of 25% water the consistency of a good filler is reached, FIX 10-M is floatable after addition of 30 - 50% water.

To FIX 10-M sand may be added, mixing ratio:
1 part FIX 10-M to 1 - 2 parts sand by volume.

Important advice:

Pilot testing is necessary.

FIX 10-M contains cement and is classified irritant according to GefStoffV.

Please observe valid EU-safety data sheet.