



## Technical Data Sheet

# REINIT-BM

**Art.-No. 4 06303**

## Machine care

### Properties and Benefits:

REINIT-BM prevents the adhesion of concrete and mortar residues, does not attack metal or lacquer. Reduces rust formation on the treated metal parts. Regular application of REINIT-BM prolongs the service life of machinery and equipment.

### Fields of Application:

REINIT-BM is to be applied, generally when adhesion of concrete or mortar should be prevented. It is especially suitable for construction machinery, mixers, automatic stone manufacturing machines, mixer trucks and tools.

### Technical Data:

Colour:	yellow
Form:	liquid
Density:	0.9 g/cm <sup>3</sup>
Storage:	protect against frost and dirt
Shelf-life:	12 months in closed original containers
Packaging:	1000 l IBCs 180 l drums 25 l cans
Consumption:	100 - 150 g/m <sup>2</sup>

### Instructions for Use:

New equipment has to be sprayed with REINIT-BM before use. Used or soiled building equipment should be cleaned with a high pressure hose before first use. Larger concrete and mortar residues must be removed mechanically and be pretreated with REINIT-R if necessary. As soon as the metal surface is dry and clean, REINIT-BM is to be applied until saturation (undiluted) by suitable painting or spraying equipment.

### Special Advice:

Our recommendations are only guidelines. Own suitability tests are absolutely necessary to achieve the correct application.

### Safety Advice:

Please adhere to the European Safety Data Sheet (MSDS)!