



Technical Data Sheet

REMISTAR

Concrete Paint for Colour Effects

Art.-No. 4 064xx

Fields of Application:

REMISTAR is especially designed for application on absorbing concrete surfaces such as for paver blocks, kerbstones and fair-faced concrete.

It is particularly suitable for hardened and absorbent substrates.

By using, REMISTAR weathered and washed-out surfaces can be revitalized in different colours.

Properties and Benefits:

REMISTAR is a solvent-free concrete paint, based on an aqueous polymeric dispersion with high-quality dyes.

REMISTAR makes it possible to design without solvent and protects the concrete from environmental influences. The texture of the so treated concrete is not covered and remains unchanged.

REMISTAR is weatherproof and UV-light resistant.

Technical Data:

Colour:	black, red, white, grey
Form:	liquid
Density:	1.1 – 1.4 g / cm ³
Storage:	in closed original containers, protect against frost and dirt
Shelf-life:	12 months
Packaging:	depending on colour type 180 kg drums 15 kg buckets 6 kg buckets

Consumption:

150 – 350 g/m²
depending on substrate and colour

Instructions for Use:

REMISTAR is supplied ready-for-use and is to be applied evenly by brush or suitable spraying device.

In each case, puddles are to be avoided during treatment!

Dirt, dust and all foreign paint substances are to be removed completely from the substrate before application.

For this procedure, we recommend REINITR, our highly-active stone cleaner, based on a fast acting, biodegradable organic acid.

Before REMISTAR is applied, the substrate should only be matt-moist at maximum.

Intense sunlight and rain must be avoided during application.

Special Advice:

- Before using a high-pressure hose for cleaning purposes, it is essential to test its effect on the product on a remote spot.
- Weathering tests show high stability.
- Avoid puddles.
- The ground has to be cleaned thoroughly before REMISTAR is applied.
- Protection against intense sunlight during and three hours after application is absolutely necessary.
- REMISTAR is not suitable for treatment on heavy-duty traffic zones.

Safety Advice:

Please adhere to the European Safety Data Sheet (MSDS)!