



## Stonecrete Sealer

1

### Acrylic Sealer

#### Product Description:

This high-performance acrylic sealer is designed to protect and enhance concrete and stone surfaces. Its advanced formula penetrates deep for superior adhesion, offering long-lasting protection against weather, stains, and UV damage. Ideal for both interior and exterior use.

#### Key Features & Benefits:

- Enhances and protects the natural beauty of
- stone and concrete.
- Resistant to stains, water, and fading.
- Easy application with a roller, sprayer, or brush.

#### Areas Of Application:

It can be applied on stone surfaces (natural and artificial), concrete, terrazzo tiles, and terracotta. It can be applied on both horizontal and vertical surfaces (floors & walls).

#### Surface Preparation:

Ensure the surface is clean, dry, and free of dust, grease, and oils. Fill and repair all cracks.

#### Application Guidelines:

- Stir or shake well before use. Apply in thin, even coats using a roller, sprayer, or brush.
- Stonecrete Sealer is ready to use. Dilution is NOT recommended.
- All tools should be cleaned with soapy water before the product dries out.

#### Coverage/ Consumption:

Theoretical Coverage is 8 to 12 m<sup>2</sup>. / Ltr. / Coat on a smooth surface.

#### Curing & Protection:

Touch Dry (25 °C)	: 3–4 hours		
Dry to recoat	: 24 hours	Dry for traffic	: Light traffic 24 Hours
			: Heavy Traffic 72 Hours

#### Packaging:

Available in 1 litre, 6 litres. and 25 litre pails.

#### Storage & Shelf life:

Store in a frost-free environment away from direct sunlight and maintain an ambient temperature of 25°C. Given these conditions, it will remain useable for 12 months in the original unopened packaging, use opened packaging promptly.



## Stonecrete Sealer

### Health & Safety:

Avoid skin and eye contact. Use gloves, goggles, and protective clothing. Ensure adequate ventilation during mixing and application. Refer to the Safety Data Sheet (SDS) for full handling and disposal information.

### Technical Data:

Property	Value
Basis	Acrylic
Colour	Clear
Consistency	Liquid
PH	7.9 ± 0.5
Specific Gravity	1.00 ± 1.0%
Brix	16%
Solid Content	24 ± 1.0%
Consumption (on a smooth surface)	8 to 12 m <sup>2</sup> . / ltr. / coat.
Dry to touch	between 3 hours to 4 hours.
Dry to recoat	24 hours
Open to traffic	Light traffic 24 hours. Normal traffic 72 hours